

SM65

Unparalleled Performance, Innovative Features, and a Great Price.

The SM 65 is, quite simply, the best value available in today's marketplace for strapping machines. At 65 straps per minute, it is lightning fast. Available in several different arch and strap sizes, the SM65 is an excellent strapper for a broad range of applications. The state of the art strapping head has 30% fewer parts than comparable strapping machines, and utilizes brushless DC motors. The result is a high speed strapping machine that consumes less power, requires fewer adjustments, and requires minimal maintenance. The extensive list of standard features on the SM65 is listed below. Plus, it's backed by the best warranties in the industry, 99% parts availability within 24 hours, and unlimited, free telephone support for the life of the machine. If you are looking for a fast, reliable strapper that is operator and maintenance friendly, you can't get a better value than the SM65.

STANDARD FEATURES OF THE SM65

- Patented Easy Strap Access
Access to the strapping channel requires no tools.
- Quick Coil Change
Strap is changed at waist height and automatically fed...no more crawling on the floor
- One Piece Strap Track
Track design eliminates dusting and guarantees parallel straps
- Sensor Controlled Heater
Heat seals are consistent and highly reliable
- Jam Free Technology
Missed straps are ejected and the SM65 returns to the ready position
- Foot Bar Switch
Provides "hands free" operation
- Adjustable Table Height
The table height is adjustable to any height between 32.3" and 36.2" (820mm-920mm)
- Photocell Activation
Several options can be programmed when this feature is activated.

OPTIONS AVAILABLE ON THE SM65

Foot pedal switch
Available in a Stainless Steel Frame

TECHNICAL SPECIFICATIONS:

All dimensions refer to an arch size of 25.6" wide (650mm) x 19.7" high (500mm)


Dimensions: 48" W x 25.6" D x 55.3" – 59.25" H
1220mm W x 650mm D x 1405-1505mm H

Weight: 352 lbs.
160 Kg

Table Height: 32.3" – 36.2" (adjustable)
820mm – 920 mm

Tension Range: 5-9mm
2 - 77 lbs
1-35 Kg
12mm
2-100 lbs
1-45Kg

Speed: Up to 65 Straps per minute



Compact strap head with brushless DC motors



Jam free technology

(technical specifications continued on reverse side)

TECHNICAL SPECIFICATIONS (continued):

Package Size: Minimum: 2.75" Wide x .75" High
70mm x 20mm
Maximum: Dependent upon arch size

Strap Size: 1/4", 3/8", 1/2"
5mm, 6mm, 9mm, 12mm

Core Size: 8" x 8"
200mm x 200mm

Power Requirements: 110V, Single Phase 50/60 Hz, 5 Amps, 220V, 230V available as an option

AVAILABLE ARCH SIZES

Arch Sizes – SM65, 1/4", 3/8" (5, 6, and 9mm)						
Width (in./mm)	21.6/550	25.6/650	33.4/850	41.3/1050	49.2/1250	64.9/1650
Height (in./mm)						
15.7/400	s		x			
19.7/500		x	x		x	x
23.6/600			x			
31.5/800			x	x	x	
39.4/1000				x	x	

S indicates standard size

Arch Sizes – SM65 1/2" (12mm)						
Width (in./mm)	21.6/550	25.6/650	33.4/850	41.3/1050	49.2/1250	64.9/1650
Height (in./mm)						
15.7/400			x			
19.7/500		s				x
23.6/600			x	x	x	
31.5/800			x	x	x	
39.4/1000			x	x	x	

S indicates standard size



Easy coil leading system



Foot bar activation



Adjustable table height

TYPAC
INC.

PO Box 425
Baldwinsville, NY 13027
800 356-8964 315 638-9431
FAX 315 638-9433
www.typac.com

